



DECLARATION OF CONFORMITY

The undersigned, representing the
Fellessons Byggnadsvaror AB

and manufacturing plant

Timber Products

Hjortvägen 3 Växjö

herewith declares that the

**Sawn, planed or profiled panelling and cladding with or without
tongue and groove with characteristics and performance
declarations as below**

Characteristic	Performance declaration
Intended use	Internal or external panelling/cladding for wall or ceiling
Species/species group	WPPA: spruce (<i>Picea abies</i>) and pine (<i>Pinus sylvestris</i>)
Growth area	NNE Europe (Northern and North Eastern Europe)
Minimum thickness	8 mm
Reaction to fire	D-s2, d0 (CWFT – EN 14915, Table 1; density 390 kg/m ³ ; minimum total thickness 12 mm, minimum thickness 8 mm)
Formaldehyde class	E1
Content of pentachlorophenol	None
Water vapour permeability	60 (see EN 14915, clause 5.4)
Sound absorption coefficient	0,10/0,30 (see EN 14915, clause 5.5)
Thermal conductivity	0,11 (see EN 14915, clause 5.6)
Natural durability class	4 (EN 350-2)

is in conformity with the provisions of the EC Directive 89/106/CEE (Construction Products Directive - CPD) and that Annex ZA of

EN 14915:2006

has been applied.

The CE marking was affixed in 2008.

Fellessons Byggnadsvaror AB

Box 3003

SE-350 33 Växjö SWEDEN

Växjö 2008-06-01


Anders Fellesson MD